

CDXconventional

DCD-AE3

Conventional Combined Rate of Rise & Fixed Temperature Heat Detector (60°C)

Features

- ▶ Electronic linear heat detection
- ▶ Remote Indicator output
- ▶ Wide voltage range (9.5 ~ 30 VDC)
- ▶ Twin fire LEDs allow 360° viewing
- ▶ Range of mounting bases
- ▶ Approved by LPCB & VdS
- ▶ Also available in white.



Description

DCD-AE3 is a Rate of Rise Heat Detector with a 60 °C fixed temperature element using a thermistor and linearising circuit to provide an accurate linear response Heat Detector.

The DCD-AE3 is ideal for use where medium ambient temperatures exist, such as drying rooms or where Smoke Detectors are unsuitable because of the presence of steam or cooking fumes such as in a kitchen.

The DCD-AE3 is supported by a range of bases for different applications and these are supported on the majority of conventional systems. A third terminal provides remote indicator output.

Specification

Ordering codes	DCD-AE3 - Ivory / DCD-AE3(WHT) - White
Operating voltage	9.5 – 30 VDC
Quiescent current	35 µA
Maximum current in alarm (typical)	40 mA
Remote indicator drive	20 mA (max) / 9.5-14 mA (typ)
IP rating	IP63
Maximum humidity	95% RH - Non condensing (at 40°C)
Operating Temperature Range	-10 °C to +50 °C
Operating Temperature Range	-30 °C to +70 °C
Colour / Case material	Ivory or White / Polycarbonate
Compatible bases	YBN-R6, YBN-R/6SK, YBO-R/6R, YBO-R/6RS, YBO-R/6RN, YBO-R/6PA
Base fixing centres (mm)	48 ~ 74
Weight (g) / Dimensions (mm)	76 / ø 100 x H 38
Approvals to (EN54:2000) Class A1 & A1R	LPCB VdS (G204044)

FIREFLY TECHNOLOGY (HONG KONG) CO., LTD

Address: Room 2914C, 29th Floor, Ho King Commercial Centre, 2-16 Fa Yuen Street, Mong Kok, Kowloon, Hong Kong
Tel: 00852 4613 9499

Email: Firely@fire-fly.hk

Website: <http://www.fire-fly.hk>